# VENUS eS5

SATA to eSATA Aluminum Enclosure

- Trayless, Hot-Swappable Drive Bays
- Supports JBOD, RAID 0, 1 and 10
- SATA Port Multiplier spec compliant
- Management Console (GUI)
- PC / Mac friendly

Included a High-Peformance PCI-E Sil3132 2-port SATA II Host Controller compatible to PC/Mac. Supports 3.0 Gbit/s SATA II speeds, Native Command Queuing, port multipliers with FIS-based switching.

Sil4726 SteelVine RAID Storage Processor

Management Console (GUI)

- Event logging
- Remote monitoring
- Manage multiple devices via GUI
- Email notification (Hardware Failure)
- JBOD, RAID 0, 1 and RAID 10
- RAID 1 modes require the daemon agent for automatic rebuild policy operation.

REAR VIEW
(8cm Cooling Fan)

VENUS eS5 (DS-315SES)

Capacity: *	up to 5TB (Terabyte)
Host Interface:	eSATA (3.0Gbit/s)
Disk Interface:	SATA connector
Disk Drive Tested:**	160GB to 1000GB HDD
Interface Transfer Rate:***	1.5Gbit/s & 3.0Gbit/s
Software:****	Management Console (GUI)
Supported RAID levels:	JBOD, RAID 0, 1, and 10
Supported OS:	Windows 2000 SP4, Windows XP Pro SP2, Windows 2003 SP1, Windows Vista / Mac OS 10.4.x
I/O Control:	Power and HDD LED
Cooling:	8cm Fan (ball-bearing)
Operating Temperature:	5 to 35 C, Humidity 20 to 80% No Condensation
Power Supply:	Auto-Switch 85 W Max (100-240Vac, 50/60Hz)
Material/Color:	Metal and ABS plastic, Black
Dimensions (LxWxH):	12.0"(L) x 7.5"(W) x 6.5"(H)
Weight:	8.3 lbs
Warranty:	1 year

www.AMSelectronics.com